

***** Capacity (BTU/Hr) *****

Ambient Temp F	Leaving Coolant Temperature												
	0	10	20	25	30	35	40	45	50	55	60	65	70
75	51,554	66,881	85,670	96,846	108,021	121,022	134,023	148,889	163,755	180,040	197,281	215,965	234,648
80	50,162	64,851	83,050	93,957	104,865	117,627	130,390	145,050	159,710	175,815	192,893	211,443	229,992
85	48,770	62,821	80,430	91,069	101,708	114,233	126,757	141,211	155,665	171,590	188,505	206,921	225,336
95		59,180	75,475	85,497	95,519	107,472	119,424	133,356	147,288	162,732	179,195	197,204	215,212
105			70,772	80,107	89,441	100,736	112,030	125,340	138,649	153,500	169,392	186,864	204,336
115					83,455	94,016	104,577	117,174	129,770	143,925	159,136	175,949	192,762

***** Power Input (Watts) *****

Ambient Temp F	Leaving Coolant Temperature												
	0	10	20	25	30	35	40	45	50	55	60	65	70
75	9,055	9,209	9,343	9,399	9,454	9,499	9,544	9,579	9,613	9,639	9,660	9,673	9,685
80	9,610	9,771	9,909	9,966	10,024	10,070	10,116	10,151	10,186	10,212	10,233	10,245	10,257
85	10,165	10,332	10,474	10,534	10,593	10,640	10,687	10,723	10,758	10,784	10,805	10,817	10,828
95		11,617	11,770	11,834	11,897	11,948	11,998	12,035	12,072	12,099	12,120	12,131	12,142
105			13,231	13,300	13,368	13,422	13,476	13,516	13,555	13,584	13,606	13,617	13,627
115					15,005	15,064	15,122	15,165	15,207	15,238	15,262	15,274	15,285

***** Current (Amps) @ 460V *****

Ambient Temp F	Leaving Coolant Temperature												
	0	10	20	25	30	35	40	45	50	55	60	65	70
75	15.7	15.9	16.0	16.1	16.1	16.2	16.2	16.3	16.3	16.3	16.3	16.3	16.3
80	16.3	16.5	16.6	16.7	16.8	16.8	16.9	16.9	16.9	16.9	16.9	16.9	16.9
85	16.9	17.1	17.2	17.3	17.4	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
95		18.5	18.7	18.8	18.9	19.0	19.0	19.0	19.0	19.0	19.1	19.1	19.0
105			20.4	20.5	20.6	20.7	20.7	20.8	20.8	20.8	20.8	20.8	20.8
115					22.5	22.6	22.7	22.8	22.8	22.8	22.8	22.8	22.8

***** Refrigerant Flow (Lbs/Hr.) *****

Ambient Temp F	Leaving Coolant Temperature												
	0	10	20	25	30	35	40	45	50	55	60	65	70
75	717	916	1,157	1,298	1,439	1,601	1,762	1,944	2,126	2,323	2,531	2,754	2,976
80	713	907	1,145	1,285	1,426	1,587	1,749	1,932	2,116	2,314	2,524	2,750	2,975
85	708	898	1,133	1,273	1,412	1,574	1,736	1,921	2,105	2,305	2,517	2,746	2,974
95		886	1,113	1,250	1,387	1,549	1,710	1,895	2,080	2,283	2,498	2,731	2,964
105			1,095	1,229	1,363	1,522	1,681	1,866	2,051	2,255	2,472	2,709	2,945
115					1,339	1,495	1,651	1,835	2,018	2,223	2,440	2,679	2,917

***** EER (Btu/Watts) *****

Ambient Temp F	Leaving Coolant Temperature												
	0	10	20	25	30	35	40	45	50	55	60	65	70
75	5.69	7.26	9.17	10.30	11.43	12.74	14.04	15.54	17.04	18.68	20.42	22.33	24.23
80	5.25	6.67	8.43	9.47	10.52	11.73	12.95	14.35	15.76	17.30	18.94	20.73	22.52
85	4.80	6.08	7.68	8.64	9.60	10.73	11.86	13.17	14.47	15.91	17.45	19.13	20.81
95		5.09	6.41	7.22	8.03	8.99	9.95	11.08	12.20	13.45	14.79	16.26	17.73
105			5.35	6.02	6.69	7.50	8.31	9.27	10.23	11.30	12.45	13.72	14.99
115					5.56	6.24	6.92	7.73	8.53	9.44	10.43	11.52	12.61